



| 型号                           | 规格                    | 圈+保持架+球                                              | 技术要求                                                                  |           |
|------------------------------|-----------------------|------------------------------------------------------|-----------------------------------------------------------------------|-----------|
| SR144-2.38 (Angular contact) | 3.175*6.35*2.38       | Stainless Steel+Torlon+Ceranic Balls                 | Inside with angular contact design, service life                      | Very long |
| SR144-2.38 (Angular contact) | 3.175*6.35*2.38       | Stainless Steel+Torlon+Ceranic Balls                 | Inside with angular contact design, service life                      | Very long |
| SR144-2.38 (Angular contact) | 3.175*6.35*2.38       | Stainless Steel+Torlon+Ceranic Balls                 | Inside with angular contact design, service life                      | Very long |
| SR144-2.38 (Angular contact) | 3.175*6.35*2.38       | Stainless Steel+Torlon+Ceranic Balls                 | Inside with angular contact design, service life                      | Very long |
| SR144-2.38 (Angular contact) | 3.175*6.35*2.38       | Stainless Steel+Torlon+Ceranic Balls                 | Inside with angular contact design, service life                      | Very long |
| S628-2.35                    | 2.35*5.5*20Wave cage) | Stainless Steel1440C+Stainless Steel1304+Steel Balls | Modify bearing internal mechanism, Enhance axial load                 |           |
| S628-2.35                    | 2.35*5.5*20Wave cage) | Stainless Steel1440C+Stainless Steel1304+Steel Balls | Modify bearing internal mechanism, Enhance axial load                 |           |
| S628-2.35                    | 2.35*5.5*20Wave cage) | Stainless Steel1440C+Stainless Steel1304+Steel Balls | Modify bearing internal mechanism, Enhance axial load                 |           |
| SR144-2.38 (Angular contact) | 3.175*6.35*2.38       | Stainless Steel+Torlon+Ceranic Balls                 | Inside with angular contact design, service life                      | Very long |
| 2.48 Stepped (Whole seals)   | 3.175*6.35*5.96*2.48  | Stainless Steel+Torlon+Ceranic Balls                 | Whole seals design,Inside with angular contact,Very long service life |           |
| 2.48 Stepped (Whole seals)   | 3.175*6.35*5.96*2.48  | Stainless Steel+Torlon+Ceranic Balls                 | Whole seals design,Inside with angular contact,Very long service life |           |
| 2.48 Stepped (Whole seals)   | 3.175*6.35*5.96*2.48  | Stainless Steel+Torlon+Ceranic Balls                 | Whole seals design,Inside with angular contact,Very long service life |           |
| SR144-2.78 (Whole seals)     | 3.175*6.35*2.38       | Stainless Steel+Torlon+Ceranic Balls                 | Whole seals design,Inside with angular contact,Very long service life |           |
| SR144-2.78 (Whole seals)     | 3.175*6.35*2.38       | Stainless Steel+Torlon+Ceranic Balls                 | Whole seals design,Inside with angular contact,Very long service life |           |
| SR144-2.78 (Whole seals)     | 3.175*6.35*2.38       | Stainless Steel+Torlon+Ceranic Balls                 | Whole seals design,Inside with angular contact,Very long service life |           |
| SR144-2.38 (Whole seals)     | 3.175*6.35*2.38       | Stainless Steel+Torlon+Ceranic Balls                 | Whole seals design,Inside with angular contact,Very long service life |           |
| SR144-2.38 (Whole seals)     | 3.175*6.35*2.38       | Stainless Steel+Torlon+Ceranic Balls                 | Whole seals design,Inside with angular contact,Very long service life |           |
| SR144-2.38 (Whole seals)     | 3.175*6.35*2.38       | Stainless Steel+Torlon+Ceranic Balls                 | Whole seals design,Inside with angular contact,Very long service life |           |
| SR144 (Full balls)           | 3.175*6.35*2.38       | Imported Stainless Steel+Imported Steel Balls        | Open type filling ball assembly method,Enhance axial load             |           |
| SR144 (Full balls)           | 3.175*6.35*2.38       | Imported Stainless Steel+Imported Steel Balls        | Open type filling ball assembly method,Enhance axial load             |           |
| SR144 (Full balls)           | 3.175*6.35*2.38       | Imported Stainless Steel+Imported Steel Balls        | Open type filling ball assembly method,Enhance axial load             |           |
| SMR85 (Full balls)           | 5*8*2                 | Imported Stainless Steel+Imported Steel Balls        | Open type filling ball assembly method,Enhance axial load             |           |
| SMR85 (Full balls)           | 5*8*2                 | Imported Stainless Steel+Imported Steel Balls        | Open type filling ball assembly method,Enhance axial load             |           |

## 特殊牙科轴承

|                    |                |                                               |                                                           |
|--------------------|----------------|-----------------------------------------------|-----------------------------------------------------------|
| SMR85 (Full balls) | 5*8*2          | Imported Stainless Steel+Imported Steel Balls | Open type filling ball assembly method,Enhance axial load |
| SMR74 □Full balls) | 4*7*2          | Imported Stainless Steel+Imported Steel Balls | Open type filling ball assembly method,Enhance axial load |
| SMR74 □Full balls) | 4*7*2          | Imported Stainless Steel+Imported Steel Balls | Open type filling ball assembly method,Enhance axial load |
| SMR74 □Full balls) | 4*7*2          | Imported Stainless Steel+Imported Steel Balls | Open type filling ball assembly method,Enhance axial load |
| SR133 □Full balls) | 2.38*4.76*2.38 | Imported Stainless Steel+Imported Steel Balls | Open type filling ball assembly method,Enhance axial load |
| SR133 □Full balls) | 2.38*4.76*2.38 | Imported Stainless Steel+Imported Steel Balls | Open type filling ball assembly method,Enhance axial load |
| SR133 □Full balls) | 2.38*4.76*2.38 | Imported Stainless Steel+Imported Steel Balls | Open type filling ball assembly method,Enhance axial load |