



Bearing NO.	Shape Dimension								Basic Load Rating(N)		Weight (kg)
	d(mm)	d(inch)	D(mm)	D(inch)	B(mm)	B(inch)	r min(mm)	r min(inch)	Dynamic(Cr)	Static(Cor)	
16100	10	0.3937	28	1.1024	8	0.3150	0.3	0.0118	5110	2380	0.0220
16101	12	0.4724	30	1.1811	8	0.3150	0.3	0.0118	5110	2380	0.0230
16001	12	0.4724	28	1.1024	7	0.2756	0.3	0.0118	4320	2250	0.0240
16002	15	0.5906	32	1.2598	8	0.3150	0.3	0.0118	5590	2840	0.0250
16003	17	0.6693	35	1.3780	8	0.3150	0.3	0.0118	6000	3250	0.0320
16004	20	0.7874	42	1.6535	8	0.3150	0.3	0.0118	6340	3790	0.0500
16005	25	0.9843	47	1.8504	8	0.3150	0.3	0.0118	6940	4600	0.0600
16006	30	1.1811	55	2.1654	9	0.3543	0.3	0.0118	9950	6530	0.0850
16007	35	1.3780	62	2.4409	9	0.3543	0.3	0.0118	10820	7830	0.1100
16008	40	1.5748	68	2.6772	9	0.3543	0.3	0.0118	11590	9130	0.1250
16009	45	1.7717	75	2.9528	10	0.3937	0.6	0.0236	11830	9880	0.1700
16010	50	1.9685	80	3.1496	10	0.3937	0.6	0.0236	12510	11100	0.1800
16011	55	2.1654	90	3.5433	11	0.4331	0.6	0.0236	19300	16300	0.2600
16012	60	2.3622	95	3.7402	11	0.4331	0.6	0.0236	20000	17500	0.2800
16013	65	2.5591	100	3.9370	11	0.4331	0.6	0.0236	21200	17800	0.3000
16014	70	2.7559	110	4.3307	13	0.5118	0.6	0.0236	26800	23600	0.433
16015	75	2.9528	115	4.5276	13	0.5118	0.6	0.0236	27600	25300	0.457